

## Honda/Acura 4-Speed, 3-Shaft, 5-Speed

### O-Ringed End Plug

#### Part No.


# 98892-02

- End Plug 14mm
- O-Rings (2) 1 Extra

**NOTE:** Fits all units with dual linear solenoids.



Some BMXA units have been found with plugs which have smaller diameter clip-grooves and narrower retainers as shown below. The Sonnax plugs will not work in these applications (**Figure 1**).



**NOTE:** Due to application variations, additional end plugs may be required. Single end plugs in all three sizes (12mm, 14mm, 15mm) are available separately. Check the Sonnax website for part numbers available through your distributor.



#### 1. Disassembly

- Remove OE retainer, set aside for reuse.
- Remove and discard OE end plug.

#### 2. Installation & Assembly

- Install Sonnax O-ring into shallow groove, which is closer to one end of the plug. The deeper groove is for retaining clip (**Figure 2**).
- Use a small amount of ATF to lubricate O-ring and end plug, then roll on clean bench to size O-ring into groove.
- Insert Sonnax O-ringed end plug, O-ring end first, into the bore. The O-ring will seal on the second wall.
- Install OE retaining clip. If the O-ring advanced beyond the second wall in the bore, carefully lever the end plug back until the retaining clip contacts the external wall.

