

Oversized Pressure Regulator & Converter Regulator Valve Kit



Part No.
73840-RK

- Converter Regulator Valve
- Oversized Pressure Regulator Valve
- Lubrication Plugs (4) 1 Extra
- Converter Regulator Spring

NOTE: Patent Nos. 6,543,472 and 6,585,002.

Tool Kit




Part No.
F-73840-TL

- Reamer
- Reamer Jig
- Guide Pin
- Drill Bits (3) For lube modification

NOTE: Sonnax "F-Tool" kits designed to service a specific bore require the VB-FIX, a self-aligning valve body reaming fixture. More information and instructions can be found online at www.sonnax.com.

Ford CD4E, Mazda LA4A-EL



1. Disassembly

- Remove OE converter regulator retainer and set aside for reuse.
- Remove and discard OE converter regulator spring and valve.
- Remove OE pressure regulator retainer, end plug and spring; set aside for reuse.
- Remove and discard OE pressure regulator valve.

2. Bore Reaming

Ream pressure regulator bore (for reaming instructions/reamer care, please visit www.sonnax.com). Sonnax reaming tool kit **F-73840-TL** and **VB-FIX** are required for this operation.

3. Installation & Assembly

- Ensure all debris has been removed from valve bore and body.
- Install Sonnax oversized pressure regulator, spring stem facing outward.
- Reinstall OE pressure regulator spring.
- Reinstall OE end plug and secure with OE retainer.
- Install Sonnax converter regulator valve, spring pocket facing outward.
- Install Sonnax OE spring, ensuring it seats in valve spring pocket.
- Secure with OE retainer.

4. Lube Circuit Modification

Though not required for Sonnax kit to operate correctly, the following modifications are recommended to increase lube and converter pressure. Drill bits are included in tool kit for this purpose.

- a. Lightly countersink (**Figure 1**) the CCX (regulated converter charge) hole approximately 1/32" deep on both sides of the transfer plate with included 5/16" drill bit. Insert the 1/4" diameter x .225" long aluminum plug and drive into hole then peen into counter sink on both sides tightly. Verify case side of plate is flush, and stone or file if necessary. Drill a .042" orifice hole through this plug. Use Sonnax .062" drill bit to taper/countersink the entry side of the .042" hole.

- b. On the transfer plate (**Figure 1**), drill a .062" hole through the indicated wall. This will connect the line pressure circuit to the differential lube circuit.
- c. On the transfer plate (**Figure 1**), drill a .052" hole through the indicated wall. This will connect the differential and front lube circuits.
- d. Drill orifices "S" and "T" on the control valve body separator plate (**Figure 2**) to .062". Insert Sonnax small aluminum pegs (.062" diameter x .075" long) into holes and peen over on both sides.

