

**Oversized 2-6
Clutch Regulator
Valve Kit**



Part No.
124740-17K

- Regulator Valve
- Gain Valve
- Spring
- End Plug

Tool Kit




Part No.
F-124740-TL17

- Reamer
- Reamer Jig
- Guide Pin

NOTE: Sonnax “F-Tool” kits designed to service a specific bore require the VB-FIX, a self-aligning valve body reaming fixture. More information and instructions can be found online at www.sonnax.com.

Ford 6F50, 6F55; GM 6T70 (Gen. 1), 6T75 (Gen. 1)



1. Disassembly

- Remove OE retaining clip and save for reuse.
- Remove and discard OE end plug, spring, regulator and gain valves.

2. Bore Reaming

Ream 2-6 clutch regulator bore (for reaming instructions/reamer care, please visit www.sonnax.com). Sonnax reaming tool kit F-124740-TL17 and VB-FIX are required for this operation.

3. Installation & Assembly

- Be certain all debris has been removed from valve bore and valve body.
- Install Sonnax spring.
- Install Sonnax regulator valve, ensuring spring seats over spring guide.
- Install Sonnax gain valve.
- Install Sonnax end plug.
- Reinstall OE retaining clip.

4. Final Testing

Vacuum testing at the port(s) indicated holds the recommended minimum 14 and 17 in-Hg.

